


# 4K H.265 Pro NVR 7000 Series



DATASHEET

## KEY FEATURES

- ▶ **Powerful Decoding Capacity** (Maximum supporting 16\*1080P or 32\*720P network cameras viewing at the same time.)
- ▶ **HDMI & VGA** (Providing both HDMI and VGA ports for users to choose according to their monitor types.)
- ▶ **4\*3.5" HDD** (4 SATA of 3.5" HDD, providing 10TB capacity for each HDD, up to 40TB total hard disk storage.)
- ▶ **Dual LAN Interfaces** (Designed for three network working modes as Multi-address, Load Balance and Net Fault-tolerance.)
- ▶ **Video Content Analysis** (With 10 detection modes, VCA greatly enhances the performance bringing comprehensive surveillance functions.)

### H.265+H.264

Smartly figure out and switch between H.264 and H.265 automatically. It will extend the days to save recording file with H.265 than with other compressions.



### Powerful Decoding Capacity

Maximum support up to 16\*1080P or 32\*720P network cameras viewing at the same time.



### 4K Video Viewing Experience

Milesight 4K H.265 Pro NVR 7000 Series supports up to 4K definition (3840\*2160, effectively four times that of Full HD ) live viewing, playback and recording, providing users with ultra-high-definition video viewing experience.



### RAID 0/1/5/6/10

RAID (Redundant Array of Independent Disks) is a method of combining hard disks as a logical unit to achieve redundancy and greater speed of writing and reading data.

RAID Type	No. of hard disk drives required	Total Storage Space
RAID 10	4, 6, 8	n/2
RAID 6	≥ 4	n-2
RAID 5	≥ 3	n-1
RAID 1	2	n/2
RAID 0	≥ 2	n

# 4K H.265 Pro NVR 7000 Series





Model		MS-N7016-UH	MS-N7032-UH
Video/Audio Input	Network Video Input	16-CH	32-CH
	Bandwidth	Incoming 160Mbps Outgoing 160Mbps	320Mbps or 200Mbps(when RAID is enabled) 256Mbps or 200Mbps(when RAID is enabled)
Video/Audio Output	HDMI Output	1-CH, Resolution: 3840x2160/60Hz, 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI Supports Audio Output	
	VGA Output	1-CH, Resolution: 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
	Dual Stream	Support	
	Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/D1/VGA/CIF/QCIF	
	Synchronous Playback	4*(30fps @8MP), 5*(30fps @6MP), 6*(20fps @5MP), 8*(20fps @4MP), 10*(30fps @3MP), 16*(30fps @1080P), 16*(30fps @720P)	4*(30fps @8MP), 5*(30fps @6MP), 6*(20fps @5MP), 8*(20fps @4MP), 10*(30fps@3MP), 16*(30fps@1080P), 32*(30fps@720P)
Video/Audio Compression	Video Compression	H.265 <sup>+</sup> /H.265(HEVC)/H.264 <sup>+</sup> /H.264	
	Audio Compression	G.711/AAC	
	Sample Rate	8KHz/16KHz	
	Synchronous Recording	16*5MP	32*5MP
Storage	SATA	4*SATA HDD(3.5")	
	Capacity	Up to 10TB capacity for each HDD	
Disk Array	Array Type	RAID0, RAID1, RAID5, RAID6, RAID10	
Recording Management	Recording Type	Continuous, Motion Detection, Alarm, Smart Event, Event (Motion Detection, Alarm, Smart Event)	
	Snapshot	Manual Snapshot	
	Playback	Video Playback, Image Playback	
Backup	Backup	Video Backup, Image Backup	
Network	Protocol	IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, NTP, SNTP, SMTP, SNMP, UPnP, NFS	
External Interface	Network Interface	2*RJ45 100M/1000M	
	Serial Interface	1*RS-485 Series Port for PTZ	
		1*RS-232 Series Port for Console	
		1*RS-485 Series Port for Keyboard	
	USB Interface	1*USB 3.0; 2*USB 2.0	
	Audio Input/Output	1*RCA/1*RCA	
Alarm Input/Output	16-CH/4-CH		
General	Compatibility	ONVIF	
	Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting	
	Keyboard Control	Milesight Keyboard (MS-K02)	
	Power Supply	AC 100V~240V 50Hz~60Hz	
	Consumption	≤15W(Without HDD)	
	Working Conditions	Temperature: -10℃~+60℃ Humidity: 10%~90%	
	Dimensions	Rack Mountable Chassis (1.5U Standard) 440mm(W)X320mm(D)X66.8mm(H)	
	Weight	4.1Kg	
	Warranty	3/5 Years	

# 4K H.265 Pro NVR 7000 Series



## Interfaces




- 1. Run Indicator    2. HDD Indicator    3. USB    4. Power Light    5. LAN1    6. LAN2    7. Audio Out    8. Audio In
- 9. RS-232    10. VGA    11. HDMI    12. USB    13. RS-485    14. Alarm Out    15. Alarm In    16. Power

## Installation of HDDs



## Structure Diagrams



Units: mm

## Naming Convention

