



Single Input High Definition DVB-T Modulator with HDMI Loop Through and IR Return Path



FEATURES

- Most cost effective fully featured HD Modulator on the market
- Single Input Digital Modulator encoding HDMI video and stereo audio signals to MPEG-4 only (H.264) DVB-T COFDM TV channels
- Compatible input resolutions 576i / 720P / 1080i & 1080P for high definition picture quality (ensure TV tuner is MPEG4/H.264 compatible)
- HDMI Input - with HDMI Loop Through for local connectivity
- IR Return Path - compatible with resi-linx RL-RF380 (Video Hub) and RL-RF210 (IR Target)
- Superior error rate (MER 39)
- Full function front LCD display with menu driven configuration
- New Zealand channel plan selectable
- 2K/8K Carriers
- Adjustment of settings available via WEB GUI
- Remote management with a PC
- Adjustable VHF / UHF Output (6-69)
- 85dB launch with Adjustable Attenuation
- Compact Design
- Silent operation - NO FAN NOISE!

SPECIFICATIONS

Number of Inputs	1
Video Encoding	MPEG -4 (H.264)
Channel Output	6 - 69
Output Connector	F type
Video & Audio Input/Output	HDMI
Video Resolution	576i / 720P / 1080i / 1080P
Output Level	85dBuV
Output Level Adjustment	20 dB typ.

