



TECHNICAL SPECIFICATION

MODEL NO: ARC-1464WP

Wall Plate Audio Amplifier with CSR Bluetooth v5.0

SPECIFICATIONS

- Audio Inputs :Bluetooth Receiver or stereo audio line level
- Bluetooth Version: Bluetooth v5.0 compliant with aptX
- Bluetooth Receive Distance: 30 Meters (open space)
- Power Amplifier Type: Stereo Class-D
- Output power: 24W(rms) per channel (@ RL=4 ohm)
- THD+N :0.1 % (@ RL=4 ohm, f = 1 kHz)
- Minimum Load Resistance :4 ohm
- Includes Speaker Protection circuit.
- Power Source:24 VDC/1.5 A
- 3 min link-lost timeout function. Bluetooth automatically switch to pairing state if reconnecting fail.
- Audio priority: BT > Line In.
- Configure Device Name & PIN Code by AT Command

Bluetooth Blue LED Status:

LED state	Statement
Blue led on : 1 sec , off : 2 sec , repeat	All profiles are standby but not connected with any Bluetooth device yet.
Blue led flash every 2 sec	A2DP or HFP is connected.
Blue led flash twice every 2 sec	On A2DP streaming state.
Blue led On: 150ms, Off: 150ms repeat	Enter pairing mode.